



Optical Breakout Cable 12E9/125µm OS2 I-V(ZN)HH bulk stock



Price: 7,12 € including 19% VAT, plus shipping costs

Price of 17. Dec. 2023, current price and availability can be viewed in the online shop.

Article: Optical Breakout Cable 12E9/125µm OS2 I-V(ZN)HH bulk stock

Part Number: 163512

Description

Indoor Breakout cable I-V(ZN)HH, non-metallic, halogenfree, gel free
suitable for connector assembly

Standards:

Flame retardant: IEC 60332-2

Low smoke: IEC 61034

Halogen free: IEC 60754-2

Transmission specifications: IEC 60793, ITU-T G.652, ITU-T G.651

Cabling: ISO 11801, EN 50173

Temperature Range: -20°C to 60°C

Specifications

Execution	indoor breakout cable I-V(ZN)HH, halogen-free, LSZH
Gradient fiber	9/125µm OS2
Number of fibers	12
Diameter	12,0mm (0.47 inch)
Coat color	yellow
Bend radius	>240mm (>9.449 inch)
Temperature range	-20°C to +60°C (-4°F to +140°F)
Ultimate Tensile Strength	2700 N
RoHS compliant	Yes
Weight	0,24 kg/m

We take no liability for the correctness and completeness of the information. Figures may vary. Change without notice.